

SOLAR PANEL



**30 YEARS PANEL
WARRANTY**



**95% SAVING ON
ELECTRICITY EXPENSES**




Ip68 Junction Box For High
Waterproof level



LCOE Is Cut Back by using M10 size solar cell
with adding more power output than lower
size cell module



Field Reliability is improved due to multiple
contact points on the cell which lowers the
cell stress during module fabrication



AR Coated Tempered Glass Anti-
Reflective Module Surface



Excellent Module Efficiency



Defects Pre and Post EL Checking to ensure
defect free module



Excellent module conversion
efficiency of up to 21.3%

 www.sunithon.com

 Support@sunithon.com

 1138 Szekszárdi utca 9, 13 kerület,
Budapest, Hungary



SONNENWERK



mono, 1/2 cut cell 166mm, 1500V, 60-cell (BS)			SU120C-BS-360		SU120C-BS-365		SU120C-BS-360		SU120C-BS-360		SU120C-BS-360	
			STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
	<u>Sonnenwerk</u>											
	NominalMax.Power	Pmax (Wp)	360	271	365	275	370	279	375	283	380	287
	Maximum Power Voltage	Vmp (V)	34.00	32.00	34.20	32.20	34.40	32.40	34.60	32.60	34.80	32.80
	Maximum Power Current	Imp (A)	10.59	8.47	10.67	8.54	10.76	8.60	10.84	8.67	10.92	8.74
	Open-Circuit Voltage	Voc (V)	40.90	38.50	41.10	38.70	41.30	38.90	41.50	39.10	41.70	39.30
	Short-Circuit Current	Isc (A)	11.40	9.12	11.50	9.20	11.60	9.28	11.70	9.36	11.80	9.44
	Module efficiency	(%)	19.76		20.04		20.31		20.59		20.86	
	Power Tolerance	Pmax (Wp)	0~+5									
	Maximum System Voltage DC	(V)	1500									
	Maximum Series Fuse Rating	(A)	20									
	Operating temperature	(°C)	-40~+85									
	Temp. coefficients of Pmax	(%/°C)	-0.370									
	Temp. coefficients of Voc	(%/°C)	-0.286									
	Temp. coefficients of Isc	(%/°C)	0.057									
	Nom. Operating cell temp. (NOCT)	(°C)	45±2									
	Cell Type		Mono 166*83mm									
	Dimensions		1755*1038*35									
	Weight		19.5 kg									
	Junction Box		IP68, 3 Bypass Diodes									
	Output Cable		350mm									
	Connector Type		PV Connector									
	Hail Resistance		distance 1m,Hail stone Diameter 25mm,Speed 23m/s									
	Wind Load		2400 Pa / 244 kg/ m²									
	Mechanical Load		5400 Pa / 550 kg/ m²									
	Packing Configuration		36/64									
	Loading Capacity (20GP)		216									
	Loading Capacity (40HQ)		832									
	Size / Pallet (mm)		1790*1140*1390/1790*1140*2415									
	Weight / Pallet		755/1354									